CENTER 232 AC/DC TRUE RMS Power Clamp Meter



LED Back Light

600V CAT III

FEATURES:

- 4 Digital Display
- TRUE RMS
- Auto Power Off
- Peak Hold Function
- Data Hold Function
- Auto Zero

SPECIFICATIONS

Function	Range	Resolution	Accuracy
ACA	600A	100mA	±2%rdg+10dgts
DCA	600A	100mA	±2%rdg+10dgts
ACV	600V	0.1V	±1.5%rdg+5dgts
DCV	600V	0.1V	±1.5%rdg+5dgts
WATT	100KW / 360KW	10W	±2%rdg+10dgts
Resistor	10KΩ	1Ω	±1.5%rdg+3dgts

Battery	1.5V, size AAA battery x 2
Dimensions	218x64x30 mm
Weight	approx.270g
Jaw Opening Diameter	30 mm

CENTER 235 AC Leakage Clamp Meter



LED Back Light

600V CAT III

FEATURES:

- 4 Digital Display
- 10uA Resolution
- Auto Power Off
- Autoranging
- Peak Hold Function
- Data Hold Function
- Auto Zero

SPECIFICATIONS

Function	Range	Resolution	Accuracy
ACmA	60mA / 600mA	10uA	±2%rdg+10dgts
ACA	10A / 100A	1mA	±2%rdg+10dgts
DCV	600V	0.1V	±1%rdg+2dgts
ACV	600V	0.1V	±1.2%rdg+5dgts
Freg	1000Hz	0.1Hz	±0.5%rdg+2dgts
Resistor	1000Ω	0.1Ω	±1%rdg+3dgts

Battery	1.5V, size AAA battery x 2
Dimensions	218x64x30 mm
Weight	approx.270g
Jaw Opening Diameter	28 mm

CENTER®

CENTER TECHNOLOGY CORP.

4/F., NO.415, Jung-Jeng Rd., 238 Shu-Lin , Taipei, Taiwan

TEL: 886-2-26763926 E-Mail : center@centertek.com FAX: 886-2-26763925 http : //www.centertek.com