## CENTER 532 UV LIGHT METER



## • FEATURE

- Measure UV Light In The Environment Monitoring And Process Control
- Removable Probe For Easy Access To The Source
- Measuring Range Fully Covering UVA And UVB
- Large LCD Display For Easy Reading
- Auto Power Off Function
- Max/Min Function

## SPECIFICATIONS

Measuring Range:

1 to 3999 uw/cm2 0.01 to 39.99 mw/cm2

Sensitivity Wavelength Region (nm):

260nm~395nm

Wavelength for Calibration (nm): 365nm

**Accuracy**: ±3%rdg ±5 dgts

Temperature characteristics:

± 0.1% /°C (away from 25°C)

**Response Time:** 0.5 sec

Light detector: UV Photo diode

Operation Temperature/ Humidity:

0°C to 40°C(32°F to 104°F); 0~80% RH

Storage Temperature/ Humidity:

-10°C to 60°C(14°F to 140°F); 0~70% RH

Over range: "-OL-" display

**Battery Type:** 1.5V type Size AA battery x 2

**Battery Life:** 80 hours approx.

Dimensions:

169mm(L) x 63mm(W) x 37mm(H) 6.7(L) x 2.5(W) x 1.5(H) inch

Weight: approx. 210g

Accessories:

User's manual, Battery, Carrying case.





Detachable & Rotatable Light Sensor

\* The specifications and other information in this catalogue are subject to change without prior notice.

