

Product Specifications

FlashCheck Min/Max Digital Alarm Thermometer

Measurement Range	-58°F to 158°F (-50°C to 70°C)
Operating Range	14°F to 122°F (-10°C to 50°C)
Accuracy	±1.0°F (-22°F to 131°F) ±0.5°C (-30°C to 55°C); otherwise ±1.8°F (±1.0°C)
Display Resolution	0.1°F/°C
Display Reading Update	17 seconds
Display Size	1.92in W x 2.08in L (49mm W x 53mm L)
Instrument Size	2.99in W x 3.74in L x 0.74in D (76mm W x 95mm L x 19mm D)
Body Casing	ABS polymer, resistant to chemicals and high impact
Sensor	Thermistor
External Probe Type/ Size	Stainless Steel, 0.7in L x 0.2in Dia (17.8mm L x 5mm Dia)
Sensor cable	9.84ft x 0.08in Dia (3 meters x 2mm Dia)
Battery	AA Battery, user replaceable
Certification / Calibration	CE mark, NIST traceable, RoHS, WEEE



Model 12217

- Minimum/Maximum memory for lowest and highest readings
- High and Low Alarms with audible buzzer and flashing red light
- Detachable external sensor with gold plated stereo jack connector
- Jumbo large LCD
- Selectable °C/°F temperature scales
- Blunt probe sensor with 10 foot (3 meter) cable
- Remaining battery indicator
- Non-volatile memory retains settings during battery swaps
- Mounts to vertical surfaces with strong built-in magnets
- Foldable stand for placement on flat surfaces

DeltaTrak manufactures products under an ISO 9001:2015
registered quality management system

SS 12217 1911

