



# SmartRock™

Wireless Concrete Sensor for Temperature and Strength Monitoring

“SmartRock has been a good investment in that it's extremely user-friendly, convenient, and saves us time on our project.”

**Allan Hayes**

Construction Quality Manager  
Regional Rail Partners



Wire-Free  
& Wireless  
Technology



Remote  
Monitoring  
Capabilities




Easy  
Activation &  
Installation



Real-Time  
Data  
Collection

SmartRock



### Overview

SmartRock is the world's leading wireless sensor for monitoring the curing and hardening of concrete. The sensor is fully-embedded and secured on the rebar, making it completely maintenance and hassle-free. Temperature data is collected at two locations in the sensors' cable and body. The strength of your in-place concrete is then calculated automatically based on the maturity method (ASTM C1074). These results are accessible in real-time and remotely through the SmartRock mobile app and on the Giatec 360™ cloud dashboard to help you make informed decisions. SmartRock's AI assistant, Roxi™, eliminates human-error by sending smart notifications and alerts to give you the upmost confidence in your mix calibration data and accuracy of strength test results.

### Features


#### Software

- Accurate real-time data display (i.e. temperature, strength, max-min values, and graphs)
- Maturity calibration database
- Free Android/iOS app with easy-to-use guide
- Project management tools including live data sharing
- Giatec 360 web-based cloud dashboard
- Proactive AI notifications of concrete pouring time and mix calibration errors
- Full PDF & CSV reporting and data exporting
- Open API integration with project management applications (i.e. Procore)

#### Hardware

- Wire-free and wireless technology
- Fast, simple, and hassle-free activation and installation
- Extended temperature cable and probe for mass concrete
- Two points of temperature measurements located in sensor cable and body
- Rugged and waterproof design
- Long battery life
- 24/7 remote monitoring capabilities with the SmartHub™ device

Conventional Methods



### Applications

- Measure temperature differentials
- Accelerate formwork removal
- Control quality in the field
- Speed up post-tensioning
- Open roads to traffic faster
- Optimize curing conditions
- Improve saw cutting time



### Technical Specifications

#### Reading Range

-22 to +181 °F (-30 to 85 °C)

#### Measurement Accuracy

± 1.8 °F (± 1°C)

#### Measurement Resolution

± 0.18 °F (± 0.1°C)

#### Measurement Frequency

Once every 15 mins  
(for 2 months of data)

#### Wireless Signal Range

Up to 40 ft (12 m)

#### Temperature Cable Length

12 in (30 cm) / 10 ft (3 m)

#### Battery Life

Up to 4 months after installation

#### Data Communication and Analysis

Free Android and iOS app  
Giatec 360 Cloud Dashboard

#### Standards

ASTM C1074 (Approved by ACI 318, CSA A23.1, most USDOT specifications)