

168L/Day Industrial Dehumidifier



PRODUCT FEATURE

- CNC processed casing, rigid & durable
- Washable coarse air filter, easy to maintain
- Panasonic compressor, CFC free refrigerant
- Vibration proof tube system
- Enhanced coil, longer lifetime
- Support external pump, RS485
- Class F fan motor, Low/High Speed
- Auto-restart, timer on/off, defrost, RH offset etc.
- Lack/Wrong Phase protection, low pressure protection etc.



Multiple Functions

Speed set, auto-restart, timer, RH offset, RS485, defrost time set, Low pressure alarm, pump alarm



Gas Charger & Low Pressure Switch

Easy for maintenance, protect compressor



Durable Tube Line Assembly

0.35mm Copper Tube
SSTL Coil Plate
Vibration Proof Tube



Drain System

Standard direct drain
support external pump drain

TECHNICAL SPECIFICATION

Model	DH-1868E	DH-8168E
Capacity (30°C, RH80%)	7L/h	7L/h
Power Source	110V/60Hz/1Ph	220V/60Hz/3Ph
Rated Install Power	2790W	2740W
Water Drain	Hose, Φ16mm/Drain Pump(optional)	Hose, Φ16mm/Drain Pump(optional)
Refrigerant	R410A/R407c	R410A/R407c
Air Flow	1600m³/h	1600m³/h
E.S.P	50Pa	50Pa
Available Ambient Temp	20-30°C	20-30°C
Weight	122kg	122kg
Available Area(H=2.6m)	<170m²	<170m²
Dimension(W*D*H)	607*500*1680mm	607*500*1680mm