

Ceiling Mounted Dehumidifier




PRODUCT FEATURE



Control Panel

LCD/LED controller+10m remote control cable, support RS485 protocol



Supply Fan

Class F high temperature supply fan, low/high air speed




Hose Drain

Standard hose drain, hard/soft pipe connection available



Unique Structure

Withdraw type compressor + coil, easy to maintain(KA-1.0BD & KA-1.0BD)



Smart Function

Automatic power memory & restart function



Pump Drain

Built-in/External drain pump available

TECHNICAL SPECIFICATION

| Model | KA-1.0BD | KA-2.0BD | KA-5.0BD | KA-7.0BD | KA-10.0CD | KA-15.0CD | KA-20.0CD |
|------------------------|----------------------|----------------------|-----------------------|-----------------------|-----------------------|-----------------------|-----------------------|
| Capacity (30°C, 80%) | 15L/Day | 40L/Day | 90L/Day | 168L/Day | 240L/Day | 336L/Day | 480L/Day |
| Power Source | 220V/50Hz | 220V/50Hz | 220V/50Hz | 220V/50Hz | 380V/50Hz | 380V/50Hz | 380V/50Hz |
| Rated Power | 320W | 760W | 1700W | 2500W | 4500W | 7100W | 9000W |
| Rated Current | 1.5A | 3.6A | 7A | 12A | 9A | 14A | 18A |
| Air Flow | 250m ³ /h | 500m ³ /h | 1200m ³ /h | 1800m ³ /h | 2400m ³ /h | 4000m ³ /h | 5000m ³ /h |
| Refrigerant | R134a | R22/R410a | R22/R410a | R22/R410a | R22/R407c | R22/R410a | R22/R407c |
| Available Area(H=2.6m) | <20m ² | <60m ² | <100m ² | <170m ² | <250m ² | <350m ² | <500m ² |
| Weight | 25kg | 42kg | 60kg | 135kg | 160kg | 180kg | 240kg |
| Dimension(mm) | 812*385*230 | 955*450*385 | 880*626*473 | 1084*820*602 | 1300*1188*606 | | |