

□ CE □ RoHS

EZ-angle for convenient operating and reading.

Ergonomic user friendly design of twin skid-proof rubber.

- Multi-Color LED Bar-Graph Readout
- 5.5% to 100% Moisture Range
- 0~1Vdc Signal Output
- Audible Alert when Value Detected
- Built-In Calibration Function
- Sturdy and Durable Moisture Probe
- CE and RoHS Approved



Specifications of M70-L

Measuring Range	5.5 to 100% H ₂ O %WME
Accuracy (at 25°C)	±1% wood scale
Indicator	High resolution LED bar-graph readout
Signification of Color-Code	Green (<16%) - Yellow - Red (>21%)
Signal Output	0 ~ 1VDC, 10 mV /%
Calibration	Auto. Temperature compensation. Built-in calibration adjustment.
Functions	**Audible alert when value detected**Low battery alarm**Automatic shutdown**Changeable moisture probes**CE and RoHS approved
Power Supply	One 9V(006P) battery
Dimensions	153 × 56 × 32mm
Weight	145g (including battery)
Accessories	No.7021 Twin electrodes type moisture probe No.704M Protecting cap No.701P/S Replacement electrodes No.765C Pouch case Instruction manual



Option Accessories *Features of moisture probes, please see page 14.

•	
No.7021	Twin electrodes type moisture probe
No.7022	Roller type moisture probe
No.7023	Deep insert type moisture probe
No.7024	Sword type moisture probe
No.7025	Deep wall type moisture probe
No.7027	Heavy puncture type moisture probe
	• • • • • • • • • • • • • • • • • • • •





