



Testo 608-H1 Thermohygrometers


CONTINUOUS INDOOR CLIMATE MONITORING

The low-budget hygrometer testo 608-H1 continuously measures humidity, temperature and dewpoint. The large display is easily legible even at a distance, the suspension and standing fixtures allow flexible positioning on a tab the wall.

Testo 608 has a max./min. value display and a battery monitor. Thanks to the long-term stable sensor, you can rely on correct measurement results even after years.



High Accuracy
±2 %RH



Continuous
Display of Temp.,
Hum. & Dewpoint



Maximum/
Minimum Values



LED Alarm Reports
Limit Value Violations



Battery Monitor



Additional
Advantages
Testo 608-H2

A PRECISE ALARM HYGROMETER, RELIABLY REPORTS HUMIDITY AND TEMPERATURE LIMIT VALUE VIOLATIONS

Technical Data

Measuring Range	
NTC	: 0 to +50°C -20 to +50°C td
Humidity Cap	: +10 to +95%RH
Accuracy ±1 Digit	
NTC	: ±0.5°C (at +25°C)
Humidity Cap	: ±3%RH (+10 to +95%RH)
Resolution	
NTC	: 0.1°C,
Humidity Cap	: 0.1%RH
Operating Temp.	: 0 to +50°C

Measuring Rate	: 18s
Storage Temperature	: -40 to +70°C
Battery Type	: 9V Block Battery
Battery Life	: Approx. 1 year
Housing Material	: ABS
Display	: LCD, 2 lines
Dimensions	: 111 x 90 x 40 mm
Weight	: 168g

FRONT VIEW



SIDE VIEW



BACK VIEW



ACEZ INSTRUMENTS PHILIPPINES CORPORATION

457-E Boni Avenue, New Zaniga, Mandaluyong City, Philippines 1550

(63) 2 8470 8068 | 8470 8069 | 8470 8071 | 8470 8072 | Fax Number: (63) 2 8470 8043

sales@acezphil.com | www.acezphil.com